

- 18-36W**
- ⊙ 隔离式/SELV
 - ⊙ 效率高达88%
 - ⊙ 紧凑型/独立式塑料外壳
 - ⊙ 输出电流纹波: $\pm 3\%$
 - ⊙ 具有三种电流选择
- ⊙ Isolated/SELV
 - ⊙ Efficiency up to 88%
 - ⊙ Compact/Independent housing
 - ⊙ Typical ripple current: $\pm 3\%$
 - ⊙ Selectable constant current output (3 in 1)



产品型号 Model No.	输入电压 Input Voltage	功率因数 Power Factor	输出功率 Output Power	输出电流 Output Current	输出电压 Output Voltage	尺寸 Dimension
CDZ-LED-18-350A-DALI	220-240V	0.95	18W max.	300mA	30-52V	103*67*31mm(A5)
				350mA		
				400mA		
CDZ-LED-24-350A-DALI	220-240V	0.95	24W max.	300mA	48-70V	103*67*31mm(A5)
				350mA		
				400mA		
CDZ-LED-24-700A-DALI	220-240V	0.95	24W max.	500mA	16-36V	103*67*31mm(A5)
				600mA		
				700mA		
CDZ-LED-36-700A-DALI	220-240V	0.95	36W max.	500mA	30-52V	103*67*31mm(A5)
				600mA		
				700mA		
CDZ-LED-18-1050A-DALI	220-240V	0.95	18W max.	800mA	8-18V	103*67*31mm(A5)
				925mA		
				1050mA		
CDZ-LED-36-1050A-DALI	220-240V	0.95	36W max.	800mA	16-36V	103*67*31mm(A5)
				925mA		
				1050mA		
CDZ-LED-24-1400A-DALI	220-240V	0.95	24W max.	1200mA	8-18V	103*67*31mm(A5)
				1300mA		
				1400mA		
CDZ-LED-36-1400A-DALI	220-240V	0.95	36W max.	1200mA	15-26V	103*67*31mm(A5)
				1300mA		
				1400mA		

